

GW

Waterproof Weighing Scale



CE OIML R76-1:2006



ISO9001


EXCELL[®]
Since 1979

FEATURES

IP68 CERTIFIED BY SGS

- ◆ Extra-large and wide LCD display (175 x 70mm) 6 digits with 55mm height
- ◆ LCD display with COOL WHITE LED backlight
- ◆ RS-232+RTC(Real Time Clock) interface
- ◆ IP 68: mist-proof, waterproof and dustproof
- ◆ Up to 1/15,000 display resolution
- ◆ Unit switch key for Kilogram (kg) and pound (lb), etc.
- ◆ Full range tare, Pre-tare, Auto zero tracking, Sampling counting, Gross/Net Indication
- ◆ Hold function, Check mode Lo / Hi / OK, Auto average unit weight, Animal scale function
- ◆ Low power indication and auto power off
- ◆ U shape stand or Sleeve connecting stand selectable.

IP68



▼ U shape stand	▼ Sleeve connecting stand

OPTION

- ◆ Wireless for distance 100M available (SPP mode supported)
- ◆ Convenient foot switch for Zero, or Tare, or Print
- ◆ RS-485 data-transfer interface

SPECIFICATION

- ◆ Operating Temperature: Non-approval model: 0°C ~ 40°C (32°F ~ 104°F)
Approval model: -10°C ~ 40°C (14°F ~ 104°F)
- ◆ Power Source: AC110V/230V (±10%) or DC 6V / 4Ah rechargeable battery
- ◆ Dimensions: 238 x 156 x 88mm (W x H x D)
- ◆ Display: LCD, 6 Digits, 55 mm (Height), COOL LIGHT LED backlight



EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel +886 2 8919 1000 Website www.excell-scale.com

Fax +886 2 8919 1177 E-mail sales@excell-scale.com