

ESN 1968 Waterproof Weighing Scale

ESW EXCELL



FEATURES

IP68 CERTIFIED BY SGS

- Sealed waterproof silica gel strip blocks water from infiltrating into the scale.
- Surrounded by waterproof grade sheeting to ensure the water free.
- 1/3,000~1/6,000 display resolution available.
- Aluminum frames coated with anti-corrosion treatment for longer lifespan.
- Stainless steel made for anti-rust.
- High speed of 24bits AD fast reacts and shortens the weighing operation duration.
- Selectable units: Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing units available.
- Low power indication and auto power off.
- Well-designed protection point for transportation.
- Concave handle for easy carrying.
- Dry battery is for LCD only and lasts for at least 200 hours with alkaline battery
- Patented structure for faster stability and zero return



Concave-in handle



Easily assemble & disassemble rechargeable battery



Easy to clean and maintain platter

SPECIFICATION

| MODEL | CAPACITY | DIVISION | RESOLUTION |
|--------|----------|----------|------------|
| ESW-3 | 3kg | 0.5g | 1/6,000 |
| | | 1g | 1/3,000 |
| ESW-6 | 6kg | 1g | 1/6,000 |
| | | 2g | 1/3,000 |
| ESW-15 | 15kg | 2g | 1/7,500 |
| | | 5g | 1/3,000 |
| ESW-30 | 30Kg | 5g | 1/6,000 |
| | | 10g | 1/3,000 |

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F) **LCD Display:** 35x108mm; 6 digits, 25mm (height), LED backlight **Power Source:** 4 x " D " Alkaline battery **Dimensions:** 240 x 117 x 280 mm (W x H x D) **Weight of the scale:** Around 3.5kg





EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan
Tel +886 2 8919 1000 Website www.excell-scale.com
Fax +886 2 8919 1177 E-mail sales@excell-scale.com