









ISO 9001



IP68 CERTIFIED BY SGS

- Sealed waterproof silica gel strip blocks water from infiltrating into the scale.
- Surrounded by waterproof grade sheeting to ensure the water free.
- 1/3,000~1/7,500 display resolution available.
- Aluminum frames coated with anti-corrosion treatment for longer lifespan.
- LED or LCD display model available.
- Stainless steel made feet and platter for anti-rust.
- High speed of 24bits AD fast reacts and shortens the weighing operation duration.
- Selectable units: Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing units available.
- Built-in rechargeable battery can be easily replaced.
- Vertical placement design battery prevents from electrolyte leakage, and makes more safety and durable.
- Low power indication and auto power off.
- Well-designed protection point for transportation.
- Securable platter with screws at users' needs.

SPECIFICATION

MODEL	CAPACITY	DIVISION	RESOLUTION
YSW-3	3kg	0.5g	1/6,000
		1g	1/3,000
YSW - 6	6kg	1g	1/6,000
		2g	1/3,000
YSW-15	15kg	2g	1/7,500
		5g	1/3,000
YSW-30	30Kg	5g	1/6,000
		10g	1/3,000

Operating Temperature : $0^{\circ}\text{C} \sim 40^{\circ}\text{C} (32^{\circ}\text{F} \sim 104^{\circ}\text{F})$

Power Source:

AC 110V~240V (±10%) adapter + DC 6V / 7Ah or


DC 6V / 4Ah rechargeable battery

Dimensions: 250.4 x 144 x 313mm (W x H x D)

Weight of the scale: Around 3kg







YSW-5C (LCD display): 109x35.5mm; 6 digits, 25mm (height), LED backlight

YSW-5E (LED display): 75.1x19mm; 6digits, 15mm (height)





EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel +886 2 8919 1000 Website www.excell-scale.com

Fax +886 2 8919 1177 E-mail sales@excell-scale.com